

SPECIALTY HEAT SHRINK PRODUCTS

GREMSPOOL® GMB / GMB A

Thin wall tubing & dual wall in a dispenser





















Features/Applications

GREMSPOOL® is a range of heat shrink tubing available in a conveniently packaged dispenser. It is specially designed to meet the requirements of wholesalers, distributors repair shops or electrical work shops.

GREMSPOOL® GMB

Contains 2:1 ratio, 125°C, flexible, flame retardant irradiated polyolefin heat shrink tubing. Refer to GREMTUBE® G55 data sheet for details.

GREMSPOOL® GMB A

Contains 3:1 ratio, 110°C, flexible, flame retardant irradiated polyolefin heat shrink tubing with adhesive.

Refer to GREMTUBE® G61A 3X data sheet for details.

Various

Available sizes:

From 1,6mm up to 25,4mm

Standard colours:

GREMSPOOL® GMB: Black, Clear, Red, Blue, Yellow, Green, White, Yellow/Green.

GREMSPOOL® GMB A: Black.

(others colours available on request)

Dimensions



Reference	As supplied (mm)	After recovery (mm)	Standard
GREMSPOOL® GMB	Inside Diameter Min. (D)	Inside Diameter Max. (d)	Dispenser Length (m)
160	1.6	0.8	15
240	2.4	1.2	15
320	3.2	1.6	15
480	4.8	2.4	12
640	6.4	3.2	12
950	9.6	4.8	8
1270	12.7	6.4	8
1910	19.1	9.5	5
2540	25.4	12.7	5

Reference	As supplied (mm)	After recovery (mm)	Standard
GREMSPOOL® GMB A	Inside Diameter Min. (D)	Inside Diameter Max. (d)	Dispenser Length (m)
300	3	1	4
600	6	2	4
900	9	3	3
1200	12	4	3
1800	18	6	2
2400	24	8	2

[•]Special printing on box and special tubing are available on request.

Recommended storage conditions: Keep in cool. dry, ventilated storage (maximum temperature of 35°C) and in closed containers.



56

