



■ SPECIFICATIONS

- Voltage Rating : 125 V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000M Ω min
- Temperature Range : - 40 $^{\circ}$ C to +105 $^{\circ}$ C
- Contact Resistance : 20m Ω max

■ TERMINAL

- Applicable Wires : AWG# 22-28
- Material : Brass
- Finish : Tin Plated; Gold Plated
- Thickness : 0.2mm
- Q' ty : 10000 pcs./Reel

Shallin Electronics Co., Ltd.

APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
林陳鏢	4:1	mm	.0 ±0.3	ECR	200511-005	05/11/22			
CHECKED BY	PROJ	VER NO.	.00 ±0.2	ECR	DG 200602-001	06/02/07			
			.000 ±0.1	ECR	DG 200610-008	06/10/27			
DRAWN BY	DATE	SIZE	ALL ±				CUSTOMER		
劉蓮花	2006/10/27	A4	ANGLE				Conforms to The RoHS Instruction		
			0 $^{\circ}$ ±						
			.0 $^{\circ}$ ±						

PART NO YY09CT
2.54mm Center Mini Latch Terminal