



■ SPECIFICATIONS

- Voltage Rating : 250V AC/DC
- Current Rating : 3A AC/DC
- Withstanding Voltage : 1000V AC/minute
- Insulation Resistance : 1000MΩ min
- Temperature Range : - 25°C to + 85°C
- Contact Resistance : 20mΩ max

■ HOUSING

- Part No. : YY2Cxx
- PolesN : 2-15
- Material : Nylon 66 UL94V-2
- Q' ty : 1000 pcs./Bag

Poles	Part No.	Dimensions(mm)	
		A	B
2	JS-8001-02	2.54	5.60
3	JS-8001-03	5.08	8.14
4	JS-8001-04	7.62	10.68
5	JS-8001-05	10.16	13.22
6	JS-8001-06	12.70	15.76
7	JS-8001-07	15.24	18.30
8	JS-8001-08	17.78	20.84
9	JS-8001-09	20.32	23.38
10	JS-8001-10	22.86	25.92
11	JS-8001-11	25.40	28.46
12	JS-8001-12	27.94	31.00
13	JS-8001-13	30.48	33.54
14	JS-8001-14	33.02	36.08
15	JS-8001-15	35.56	38.62

PART NO YY2Cxx		APPROVED BY	SCALE	UNIT	TOLERANCE	LTR	REVISION RECORD	DATE	LTR	REVISION RECORD	DATE
			4:1	mm	.0 ±0.3	ECR	RoHS Compliant	06/09/20			
2.54mm Crimp Style Connectors Housing		CHECKED BY	PROJ	VER NO.	.00 ±0.2	ECR	DG 200609-004	06/09/20			
					.000 ±0.1						
		DRAWN BY	DATE	SIZE	ALL ±				CUSTOMER		
			2006/09/20	A4	ANGLE	0° ±				Conforms to The RoHS Instruction	
					.0° ±						