


SPLASH CENTER SPRAY ETCHING MACHINE



A professional unit that integrates all important steps of PCB wet processing.

Spray etching compartment:

- Professional spray etching technology
- 100 µm line definition
- 23 µm/min etching speed with standard Fe-III-Cl
- Max. board size 210 x 300 mm
- Powerful spray pump for all types of etchants
- Built-in 1000 W heater
- Thermostat controlled
- Overheat protection
- Security lid switch
- Digital timer with count-down, auto-reset and beeper
- Also suitable for spray developing

Four Treatment tanks (from left to right side):

- Pre rinse
- Fresh water spray rinse (including magn. valve and foot-switch)
- Tank with filter basket and bath movement by pump, for resist stripping or developing
- Spare tank, i.e. for chemical security tray

Features

- All bathes covered by lids
- All bathes can be emptied by front integrated cog-valves
- PCBs may pass all wet processing steps in one PCB holder
- Inclusive anti-pollution security tray

Technical data

- **Power supply:**
230 V~, 50 Hz approx. 1150 VA
- **Dimensions (L x W x H):**
100 cm x 67 cm x 121 cm
- **Tank capacity:**
1 x 25 l + 3 x 7 l + 1 x 9 l
- **Weight:**
46kg
- **Warranty:**
12 months on parts and labour

Cypax a/s ☐
www.cypax.com ☐
9710 1188